

Page 1 of 33
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
Revision date / version: 28.02.2025 / 0025
Replacing version dated / version: 04.11.2024 / 0024
Valid from: 28.02.2025
PDF print date: 28.02.2025
Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
400 ml Art.: 6210 2416, Art.: 6214 2416

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

**Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
400 ml Art.: 6210 2416, Art.: 6214 2416**

1.2 Relevant identified uses of the substance or mixture and uses advised against Relevant identified uses of the substance or mixture:

Lacquer spray

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG
Theo-Förch-Str. 11 – 15
74196 Neuenstadt
Tel.: 07139/95-0
Fax: 07139/95-199
Email: info@foerch.de
Homepage: www.foerch.com

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (TFC)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Eye Irrit.	2	H319-Causes serious eye irritation.
STOT SE	3	H336-May cause drowsiness or dizziness.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.
Aerosol	1	H222-Extremely flammable aerosol.
Aerosol	1	H229-Pressurised container: May burst if heated.

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.02.2025 / 0025
 Replacing version dated / version: 04.11.2024 / 0024
 Valid from: 28.02.2025
 PDF print date: 28.02.2025
 Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
 400 ml Art.: 6210 2416, Art.: 6214 2416



Danger

H319-Causes serious eye irritation. H336-May cause drowsiness or dizziness. H412-Harmful to aquatic life with long lasting effects. H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use. P261-Avoid breathing vapours or spray. P273-Avoid release to the environment. P280-Wear eye protection / face protection.
 P312-Call a POISON CENTRE / doctor if you feel unwell.
 P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

EUH066-Repeated exposure may cause skin dryness or cracking.
 EUH211-Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Without adequate ventilation, formation of explosive mixtures may be possible.
 n-butyl acetate
 Acetone
 2-methoxy-1-methylethyl acetate

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
 The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).
 The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).
 Dangerous vapours heavier than air.

SECTION 3: Composition/information on ingredients

3.1 Substances

n.a.

3.2 Mixtures

Acetone	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119471330-49-XXXX
Index	606-001-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	200-662-2
CAS	67-64-1
content %	20-30
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336

Dimethyl ether	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119472128-37-XXXX
Index	603-019-00-8
EINECS, ELINCS, NLP, REACH-IT List-No.	204-065-8
CAS	115-10-6
content %	10-20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Gas 1A, H220

n-butyl acetate	Substance for which an EU exposure limit value applies.
-----------------	---

Page 3 of 33
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.02.2025 / 0025
 Replacing version dated / version: 04.11.2024 / 0024
 Valid from: 28.02.2025
 PDF print date: 28.02.2025
 Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
 400 ml Art.: 6210 2416, Art.: 6214 2416

Registration number (REACH)	01-2119485493-29-XXXX
Index	607-025-00-1
EINECS, ELINCS, NLP, REACH-IT List-No.	204-658-1
CAS	123-86-4
content %	10-20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Flam. Liq. 3, H226 STOT SE 3, H336

Reaction mass of ethylbenzene and xylene	Substance for which an EU exposure limit value applies.
Registration number (REACH)	01-2119488216-32-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	905-588-0
CAS	---
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 3, H226 Acute Tox. 4, H312 Acute Tox. 4, H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 STOT RE 2, H373 (organs of hearing) Asp. Tox. 1, H304
Specific Concentration Limits and ATE	ATE (dermal): 1100 mg/kg ATE (as inhalation, Dusts or mist): 1,5 mg/l/4h ATE (as inhalation, Vapours): 11 mg/l/4h

2-methoxy-1-methylethyl acetate	Substance for which an EU exposure limit value applies.
Registration number (REACH)	---
Index	607-195-00-7
EINECS, ELINCS, NLP, REACH-IT List-No.	203-603-9
CAS	108-65-6
content %	1-<10
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 3, H226 STOT SE 3, H336

Ethanol	
Registration number (REACH)	---
Index	603-002-00-5
EINECS, ELINCS, NLP, REACH-IT List-No.	200-578-6
CAS	64-17-5
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Flam. Liq. 2, H225 Eye Irrit. 2, H319
Specific Concentration Limits and ATE	Eye Irrit. 2, H319: >=50 %

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)	
Registration number (REACH)	---
Index	022-006-00-2
EINECS, ELINCS, NLP, REACH-IT List-No.	236-675-5
CAS	13463-67-7
content %	1-<5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Carc. 2, H351 (as inhalation)

Trizinc bis(orthophosphate)	
Registration number (REACH)	---
Index	030-011-00-6
EINECS, ELINCS, NLP, REACH-IT List-No.	231-944-3
CAS	7779-90-0
content %	1-<2,5
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Aquatic Acute 1, H400 (M=1) Aquatic Chronic 1, H410 (M=1)

Alcohols, C12-14, ethoxylated	
-------------------------------	--

GB

Page 4 of 33
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.02.2025 / 0025
 Replacing version dated / version: 04.11.2024 / 0024
 Valid from: 28.02.2025
 PDF print date: 28.02.2025
 Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
 400 ml Art.: 6210 2416, Art.: 6214 2416

Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	---
CAS	---
content %	0,1-<1
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=1)

Impurities, test data and additional information may have been taken into account in classifying and labelling the product.
 For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
 The substances named in this section are given with their actual, appropriate classification!
 For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.
 The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!
 Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.
 Supply person with fresh air and consult doctor according to symptoms.
 If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

Eye contact

Remove contact lenses.
 Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Rinse the mouth thoroughly with water.
 Give copious water to drink - consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

- Irritation of the respiratory tract
- Headaches
- Dizziness
- Nausea
- Effects/damages the central nervous system
- Coordination disorders
- Unconsciousness
- With long-term contact:
 Product removes fat.
 Dermatitis (skin inflammation)

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

- Sand
- CO2
- Extinction powder

Unsuitable extinguishing media

- Water
- High volume water jet

5.2 Special hazards arising from the substance or mixture

Page 5 of 33
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
Revision date / version: 28.02.2025 / 0025
Replacing version dated / version: 04.11.2024 / 0024
Valid from: 28.02.2025
PDF print date: 28.02.2025
Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
400 ml Art.: 6210 2416, Art.: 6214 2416

In case of fire the following can develop:

Oxides of carbon
Oxides of nitrogen
Toxic gases

Danger of bursting (explosion) when heated
Explosive vapour/air or gas/air mixtures.

5.3 Advice for firefighters

For personal protective equipment see Section 8.
In case of fire and/or explosion do not breathe fumes.
Protective respirator with independent air supply.
Cool container at risk with water.
Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.
Ensure sufficient ventilation, remove sources of ignition.
Avoid dust formation with solid or powder products.
Leave the danger zone if possible, use existing emergency plans if necessary.
Remove possible causes of ignition - do not smoke.
Ensure sufficient supply of air.
Avoid inhalation, and contact with eyes or skin.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

If leakage occurs, dam up.
Resolve leaks if this possible without risk.
Prevent from entering drainage system.
Prevent surface and ground-water infiltration, as well as ground penetration.
If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available.
Active substance:
Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.
Do not wash away with water or watery cleaning agents.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation.
Room ventilation also at ground level.
Keep away from sources of ignition - Do not smoke.
Take precautions against electrostatic charges.
Do not use on hot surfaces.
Avoid inhalation of the vapours.
Avoid contact with eyes or skin.
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.
Observe directions on label and instructions for use.
Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Page 6 of 33
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.02.2025 / 0025
 Replacing version dated / version: 04.11.2024 / 0024
 Valid from: 28.02.2025
 PDF print date: 28.02.2025
 Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
 400 ml Art.: 6210 2416, Art.: 6214 2416

Keep out of access to unauthorised individuals.
 Store product closed and only in original packing.
 Not to be stored in gangways or stair wells.
 Observe special regulations for aerosols!
 Observe special storage conditions.
 Do not store with flammable or self-igniting materials.
 Keep protected from direct sunlight and temperatures over 50°C.
 Store cool.
 Store in a well ventilated place.
 Store in a dry place.

7.3 Specific end use(s)

No information available at present.
 Observe the instructions for good working practice and the recommendations for risk assessment.
 Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries, depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Chemical Name		Acetone	
WEL-TWA: 500 ppm (1210 mg/m ³) (WEL-TWA, EU)	WEL-STEL: 1500 ppm (3620 mg/m ³) (WEL-STEL)	---	
Monitoring procedures:	<ul style="list-style-type: none"> - Draeger - Acetone 100/b (CH 22 901) - Draeger - Acetone 40/a (5) (81 03 381) - Compur - KITA-102 SA (548 534) - Compur - KITA-102 SC (548 550) - Compur - KITA-102 SD (551 109) - INSHT MTA/MA-031/A96 (Determination of ketones (acetone, methyl ethyl ketone, methyl isobutyl ketone) in air - Charcoal tube method / Gas chromatography) - 1996 - EU project BC/CEN/ENTR/000/2002-16 card 67-1 (2004) - MDHS 72 (Volatile organic compounds in air – Laboratory method using pumped solid sorbent tubes, thermal desorption and gas chromatography) - 1993 - NIOSH 1300 (KETONES I) - 1994 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - NIOSH 2555 (KETONES I) - 2003 - NIOSH 3800 (ORGANIC AND INORGANIC GASES BY EXTRACTIVE FTIR SPECTROMETRY) - 2016 - OSHA 69 (Acetone) - 1988 		
BMGV: ---	Other information: ---		
Chemical Name		Dimethyl ether	
WEL-TWA: 400 ppm (766 mg/m ³) (WEL-TWA), 1000 ppm (1920 mg/m ³) (EU)	WEL-STEL: 500 ppm (958 mg/m ³) (WEL-STEL)	---	
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-123 S (549 129) 		
BMGV: ---	Other information: ---		
Chemical Name		n-butyl acetate	
WEL-TWA: 150 ppm (724 mg/m ³) (WEL-TWA), 50 ppm (241 mg/m ³) (EU)	WEL-STEL: 200 ppm (966 mg/m ³) (WEL-STEL), 150 ppm (723 mg/m ³) (EU)	---	
Monitoring procedures:	<ul style="list-style-type: none"> - Compur - KITA-138 U (548 857) - Compur - KITA-139 SB(C) (549 731) - NIOSH 1450 (ESTERS 1) - 2003 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - OSHA 1009 (n-Butyl Acetate Isobutyl Acetate sec-Butyl Acetate tert-Butyl Acetate) - 2007 		
BMGV: ---	Other information: ---		
Chemical Name		Reaction mass of ethylbenzene and xylene	
WEL-TWA: 220 mg/m ³ (50 ppm) (WEL-TWA), 50 ppm (221 mg/m ³) (EU) (Xylene) / 441mg/m ³ (100 ppm) (WEL-TWA), 100 ppm (442 mg/m ³) (EU) (Ethylbenzene)	WEL-STEL: 441 mg/m ³ (100 ppm) (WEL-STEL), 100 ppm (442 mg/m ³) (EU) (Xylene) / 552 mg/m ³ (125 ppm) (WEL-STEL), 200 ppm (884 mg/m ³) (EU) (Ethylbenzene)	---	
Monitoring procedures:	<ul style="list-style-type: none"> - INSHT MTA/MA-030/A92 (Determination of aromatic hydrocarbons (benzene, toluene, ethylbenzene, p-xylene, 1,2,4-trimethylbenzene) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 47-1 (2004) - OSHA 1002 (Xylenes (o-, m-, p-isomers) Ethylbenzene) - 1999 		

Page 7 of 33
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.02.2025 / 0025
 Replacing version dated / version: 04.11.2024 / 0024
 Valid from: 28.02.2025
 PDF print date: 28.02.2025
 Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
 400 ml Art.: 6210 2416, Art.: 6214 2416

INSHT MTA/MA-030/A92 (Determination of aromatic hydrocarbons (benzene, toluene, ethylbenzene, p-xylene, 1,2,4-trimethylbenzene) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 54-1 (2004) - OSHA 1020 (Trimethylbenzene (mixed isomers)) - 2016 - OSHA PV2091 (Trimethylbenzenes) - 1987 - Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581)	
BMGV: 650 mmol methyl hippuric acid/mol creatinine in urine, post shift (Xylene, o-, m-, p- or mixed isomers) (BMGV) (Xylene)	Other information: Sk (WEL) (Xylene) / Sk (WEL) (Ethylbenzene)

Chemical Name 2-methoxy-1-methylethyl acetate	
WEL-TWA: 50 ppm (274 mg/m ³) (WEL-TWA), 50 ppm (275 mg/m ³) (EU)	WEL-STEL: 100 ppm (548 mg/m ³) (WEL-STEL), 100 ppm (550 mg/m ³) (EU)
Monitoring procedures:	INSHT MTA/MA-024/A92 (Determination of esters II (1-methoxy-2-propyl acetate, 2-ethoxyethyl acetate) in air - Charcoal tube method / Gas chromatography) - 1992 - EU project BC/CEN/ENTR/000/2002-16 card 15-1 (2004) - NIOSH 2554 (GLYCOL ETHERS) - 2003 - OSHA 99 (Propylene Glycol Monomethyl Ethers/Acetates) - 1993
BMGV: ---	Other information: Sk (WEL)

Chemical Name Ethanol	
WEL-TWA: 1000 ppm (1920 mg/m ³)	WEL-STEL: ---
Monitoring procedures:	- Draeger - Alcohol 25/a Ethanol (81 01 631) - Compur - KITA-104 SA (549 210) - DFG (D) (Loesungsmittelgemische), Methode Nr. 6 DFG (E) (Solvent mixtures) - 2013, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 63-2 (2004) - DFG Meth. Nr. 2 (D) (Loesungsmittelgemische) - 2013 - EU project BC/CEN/ENTR/000/2002-16 card 63-2 (2004) - DFG Meth. Nr. 3 (D) (Loesungsmittelgemische) - 2013 - EU project BC/CEN/ENTR/000/2002-16 card 63-2 (2004)
BMGV: ---	Other information: ---

Chemical Name Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)	
WEL-TWA: 10 mg/m ³ (total inhalable dust), 4 mg/m ³ (respirable dust)	WEL-STEL: ---
Monitoring procedures:	---
BMGV: ---	Other information: ---

Chemical Name Butane	
WEL-TWA: 600 ppm (1450 mg/m ³)	WEL-STEL: 750 ppm (1810 mg/m ³)
Monitoring procedures:	- Compur - KITA-221 SA (549 459) - OSHA PV2010 (n-Butane) - 1993
BMGV: ---	Other information: ---

Chemical Name Propane	
WEL-TWA: 1000 ppm (ACGIH)	WEL-STEL: ---
Monitoring procedures:	- Compur - KITA-125 SA (549 954) - OSHA PV2077 (Propane) - 1990
BMGV: ---	Other information: ---

Chemical Name Isobutane	
WEL-TWA: 1000 ppm (EX) (ACGIH)	WEL-STEL: ---
Monitoring procedures:	- Compur - KITA-113 SB(C) (549 368)
BMGV: ---	Other information: ---

Acetone						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - marine		PNEC	1,06	mg/l	Assessment factor 500
	Environment - freshwater		PNEC	10,6	mg/l	Assessment factor 50
	Environment - sediment, freshwater		PNEC	30,4	mg/kg dw	
	Environment - sediment, marine		PNEC	3,04	mg/kg dw	

Page 8 of 33
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.02.2025 / 0025
 Replacing version dated / version: 04.11.2024 / 0024
 Valid from: 28.02.2025
 PDF print date: 28.02.2025
 Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
 400 ml Art.: 6210 2416, Art.: 6214 2416

	Environment - soil		PNEC	29,5	mg/kg dw	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sporadic (intermittent) release		PNEC	21	mg/l	Assessment factor 100
Consumer	Human - oral	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assessment factor 2
Consumer	Human - dermal	Long term, systemic effects	DNEL	62	mg/kg bw/day	Overall assessment factor 20
Consumer	Human - inhalation	Long term, systemic effects	DNEL	200	mg/m3	Overall assessment factor 5
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	186	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	2420	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1210	mg/m3	

Dimethyl ether						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,155	mg/l	
	Environment - sediment, freshwater		PNEC	0,681	mg/kg	
	Environment - soil		PNEC	0,045	mg/kg	
	Environment - sewage treatment plant		PNEC	160	mg/l	
	Environment - marine		PNEC	0,016	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	1,549	mg/l	
	Environment - sediment, marine		PNEC	0,069	mg/kg	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	471	mg/m3	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	1894	mg/m3	

n-butyl acetate						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,18	mg/l	
	Environment - marine		PNEC	0,018	mg/l	
	Environment - periodic release		PNEC	0,36	mg/l	
	Environment - sediment, freshwater		PNEC	0,981	mg/kg	
	Environment - sediment, marine		PNEC	0,0981	mg/kg	
	Environment - soil		PNEC	0,0903	mg/kg	
	Environment - sewage treatment plant		PNEC	35,6	mg/l	
Consumer	Human - dermal	Long term, systemic effects	DNEL	6	mg/kg	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	300	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	35,7	mg/m3	

Page 9 of 33
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.02.2025 / 0025
 Replacing version dated / version: 04.11.2024 / 0024
 Valid from: 28.02.2025
 PDF print date: 28.02.2025
 Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
 400 ml Art.: 6210 2416, Art.: 6214 2416

Consumer	Human - dermal	Short term, systemic effects	DNEL	6	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	2	mg/kg bw/day	
Consumer	Human - oral	Short term, systemic effects	DNEL	2	mg/kg bw/day	
Consumer	Human - inhalation	Short term, local effects	DNEL	300	mg/m ³	
Consumer	Human - inhalation	Long term, local effects	DNEL	35,7	mg/m ³	
Workers / employees	Human - dermal	Long term, local effects	DNEL	11	mg/kg body weight/day	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	600	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	300	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	11	mg/kg bw/d	
Workers / employees	Human - dermal	Short term, systemic effects	DNEL	11	mg/kg bw/day	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	600	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	300	mg/m ³	

Reaction mass of ethylbenzene and xylene

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,327	mg/l	
	Environment - marine		PNEC	0,327	mg/l	
	Environment - sewage treatment plant		PNEC	6,58	mg/l	
	Environment - sediment, freshwater		PNEC	12,46	mg/kg dw	
	Environment - sediment, marine		PNEC	12,46	mg/kg dw	
	Environment - soil		PNEC	2,31	mg/kg dw	
Consumer	Human - oral	Long term, systemic effects	DNEL	12,5	mg/kg bw/d	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	65,3	mg/m ³	
Consumer	Human - inhalation	Short term, systemic effects	DNEL	260	mg/m ³	
Consumer	Human - inhalation	Long term, local effects	DNEL	65,3	mg/m ³	
Consumer	Human - inhalation	Short term, local effects	DNEL	260	mg/m ³	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	211	mg/m ³	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	221	mg/m ³	
Workers / employees	Human - inhalation	Short term, systemic effects	DNEL	442	mg/m ³	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	125	mg/kg bw/d	

2-methoxy-1-methylethyl acetate

Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,635	mg/l	
	Environment - marine		PNEC	0,0635	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment, freshwater		PNEC	3,29	mg/kg dw	

Page 10 of 33
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.02.2025 / 0025
 Replacing version dated / version: 04.11.2024 / 0024
 Valid from: 28.02.2025
 PDF print date: 28.02.2025
 Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
 400 ml Art.: 6210 2416, Art.: 6214 2416

	Environment - sediment, marine		PNEC	0,329	mg/kg dw	
	Environment - soil		PNEC	0,29	mg/kg dw	
	Environment - oral (animal feed)		PNEC	6,35	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	6,35	mg/l	
Consumer	Human - oral	Short term, systemic effects	DNEL	500	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	33	mg/m3	
Consumer	Human - dermal	Long term, systemic effects	DNEL	320	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	36	mg/kg bw/day	
Consumer	Human - inhalation	Long term, local effects	DNEL	33	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	796	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	275	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	550	mg/m3	

Ethanol						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	0,96	mg/l	
	Environment - marine		PNEC	0,79	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	2,75	mg/l	
	Environment - sewage treatment plant		PNEC	580	mg/l	
	Environment - sediment, freshwater		PNEC	3,6	mg/kg dry weight	
	Environment - soil		PNEC	0,63	mg/kg dry weight	
	Environment - oral (animal feed)		PNEC	0,38	g/kg feed	
	Environment - sediment, marine		PNEC	2,9	mg/kg dry weight	
Consumer	Human - dermal	Short term, local effects	DNEL	950	mg/m3	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	114	mg/m3	
Consumer	Human - oral	Long term, systemic effects	DNEL	87	mg/kg	
Consumer	Human - dermal	Long term, systemic effects	DNEL	206	mg/kg bw/d	
Consumer	Human - inhalation	Short term, local effects	DNEL	950	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	343	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	950	mg/m3	
Workers / employees	Human - inhalation	Short term, local effects	DNEL	1900	mg/m3	

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note

Page 11 of 33
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.02.2025 / 0025
 Replacing version dated / version: 04.11.2024 / 0024
 Valid from: 28.02.2025
 PDF print date: 28.02.2025
 Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
 400 ml Art.: 6210 2416, Art.: 6214 2416

	Environment - freshwater		PNEC	0,184	mg/l	
	Environment - marine		PNEC	0,0184	mg/l	
	Environment - water, sporadic (intermittent) release		PNEC	0,193	mg/l	
	Environment - sewage treatment plant		PNEC	100	mg/l	
	Environment - sediment, freshwater		PNEC	1000	mg/kg dw	
	Environment - sediment, marine		PNEC	100	mg/kg dw	
	Environment - soil		PNEC	100	mg/kg dw	
	Environment - oral (animal feed)		PNEC	1667	mg/kg feed	
Consumer	Human - oral	Long term, systemic effects	DNEL	700	mg/kg bw/d	
Workers / employees	Human - inhalation	Long term, local effects	DNEL	10	mg/m3	

Trizinc bis(orthophosphate)						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	20,6	µg/l	Zn
	Environment - marine		PNEC	6,1	µg/l	Zn
	Environment - sediment, freshwater		PNEC	117,8	mg/kg dry weight	Zn
	Environment - sediment, marine		PNEC	56,5	mg/kg dry weight	Zn
	Environment - soil		PNEC	35,6	mg/kg dw	Zn
	Environment - sewage treatment plant		PNEC	100	µg/l	Zn
Consumer	Human - dermal	Long term, systemic effects	DNEL	83	mg/kg bw/day	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	2,5	mg/kg bw/day	
Consumer	Human - oral	Long term, systemic effects	DNEL	0,83	mg/kg bw/day	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	83	mg/kg bw/day	Zn, soluble
Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	5	mg/m3	Zn, insoluble

(8) - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |
 | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
 (8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |
 | BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
 (EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
 | Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
 (EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU, 2019/1831/EU or 2024/869/EU:
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (98/24/EC, 2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE), (15) = Substantial contribution to the total body burden via dermal exposure possible. |

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.

If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.

Applies only if maximum permissible exposure values are listed here.

Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.

These are specified by e.g. EN 14042.

EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.

Wash hands before breaks and at end of work.

Keep away from food, drink and animal feedingstuffs.

Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:

Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:

Chemical resistant protective gloves (EN ISO 374).

Protective gloves made of butyl (EN ISO 374).

Minimum layer thickness in mm:

0,4

Permeation time (penetration time) in minutes:

40

Protective hand cream recommended.

The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.

The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:

Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:

Normally not necessary.

If OES or MEL is exceeded.

Gas mask filter AX (EN 14387), code colour brown.

Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:

Not applicable

Additional information on hand protection - No tests have been performed.

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.

Selection of materials derived from glove manufacturer's indications.

Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.

Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.

In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.

The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical state:

Aerosol. Active substance: liquid.

Colour:

According to specification

Odour:

Characteristic

Melting point/freezing point:

There is no information available on this parameter.

Boiling point or initial boiling point and boiling range:

n.a.

Flammability:

Does not apply to aerosols.

Lower explosion limit:

1,2 Vol-%

Upper explosion limit:

26,2 Vol-%

Page 13 of 33
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.02.2025 / 0025
 Replacing version dated / version: 04.11.2024 / 0024
 Valid from: 28.02.2025
 PDF print date: 28.02.2025
 Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
 400 ml Art.: 6210 2416, Art.: 6214 2416

Flash point:	Does not apply to aerosols.
Auto-ignition temperature:	240 °C
Decomposition temperature:	There is no information available on this parameter.
pH:	Mixture is non-soluble (in water).
Kinematic viscosity:	Does not apply to aerosols.
Solubility:	Not miscible
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	4000 hPa (20°C)
Density and/or relative density:	0,8 g/cm ³ (20°C)
Relative vapour density:	Does not apply to aerosols.
Particle characteristics:	Does not apply to aerosols.
9.2 Other information	
Explosives:	Product is not explosive. Possible build up of explosive/highly flammable vapour/air mixture.
Oxidising liquids:	No
Evaporation rate:	n.a.
Solvents content:	72,86 % (Organic solvents)

SECTION 10: Stability and reactivity

10.1 Reactivity

Not to be expected
The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources
Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
400 ml Art.: 6210 2416, Art.: 6214 2416

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						n.d.a.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

Acetone

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
-------------------	----------	-------	------	----------	-------------	-------

Page 14 of 33
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.02.2025 / 0025
 Replacing version dated / version: 04.11.2024 / 0024
 Valid from: 28.02.2025
 PDF print date: 28.02.2025
 Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
 400 ml Art.: 6210 2416, Art.: 6214 2416

Acute toxicity, by oral route:	LD50	5800-7190	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>15800	mg/kg	Rat		
Acute toxicity, by inhalation:	LC50	76	mg/l/4h	Rat		
Skin corrosion/irritation:				Guinea pig		Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitising
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Carcinogenicity:				Mouse		Negative, References
Reproductive toxicity (Developmental toxicity):	NOAEC	2200	ppm	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						STOT SE 3, H336, May cause drowsiness or dizziness.
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	900	mg/kg bw/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	
Symptoms:						unconsciousness, vomiting, headaches, gastrointestinal disturbances, fatigue, mucous membrane irritation, dizziness, nausea, drowsiness

Dimethyl ether						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	164	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Respiratory or skin sensitisation:						No (skin contact)
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative

Page 15 of 33
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.02.2025 / 0025
 Replacing version dated / version: 04.11.2024 / 0024
 Valid from: 28.02.2025
 PDF print date: 28.02.2025
 Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
 400 ml Art.: 6210 2416, Art.: 6214 2416

Germ cell mutagenicity:					OECD 477 (Genetic Toxicology - Sex-Linked Recessive Lethal Test in Drosophila melanogaster)	Negative
Carcinogenicity:	NOAEC	47000	mg/m3	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Negative
Reproductive toxicity:	NOAEL	5000	ppm	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEC	47106	mg/kg	Rat	OECD 452 (Chronic Toxicity Studies)	Negative(2 a)
Aspiration hazard:						No

n-butyl acetate						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	10760-13100	mg/kg	Rat	OECD 423 (Acute Oral Toxicity - Acute Toxic Class Method)	Female
Acute toxicity, by dermal route:	LD50	>17600	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>21,1	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant, Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Reproductive toxicity:	NOAEC	9640	mg/m3		OECD 416 (Two-generation Reproduction Toxicity Study)	Negative
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness., STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):						Negative
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	125	mg/kg	Rat	Regulation (EC) 440/2008 B.26 (SUB-CHRONIC ORAL TOXICITY TEST REPEATED DOSE 90 - DAY (RODENTS))	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	500	ppm	Rat		

Page 16 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 28.02.2025 / 0025

Replacing version dated / version: 04.11.2024 / 0024

Valid from: 28.02.2025

PDF print date: 28.02.2025

Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222

400 ml Art.: 6210 2416, Art.: 6214 2416

Symptoms:						unconsciousness , headaches, mucous membrane irritation, dizziness, nausea and vomiting.
-----------	--	--	--	--	--	--

Reaction mass of ethylbenzene and xylene

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	3523-4000	mg/kg	Rat	Regulation (EC) 440/2008 B.1 (ACUTE ORAL TOXICITY)	
Acute toxicity, by dermal route:	ATE	1100	mg/kg			
Acute toxicity, by inhalation:	ATE	11	mg/l/4h			Vapours
Acute toxicity, by inhalation:	ATE	1,5	mg/l/4h			Dusts or mist
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Irritation of the respiratory tract, STOT SE 3, H335
Symptoms:						drowsiness, headaches, fatigue, dizziness, unconsciousness , nausea and vomiting.

2-methoxy-1-methylethyl acetate

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>23,5	mg/l/6h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative Chinese hamster
Germ cell mutagenicity:				Rat	OECD 482 (Gen. Tox. - DNA Damage and Repair, Unscheduled DNA Synthesis in Mammalian Cells In Vitro)	Negative
Carcinogenicity:	NOAEL	~ 3690	mg/m3	Rat		Analogous conclusion vapour
Reproductive toxicity:	NOAEL	300-1000	ppm	Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	Analogous conclusion vapour

Page 17 of 33
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.02.2025 / 0025
 Replacing version dated / version: 04.11.2024 / 0024
 Valid from: 28.02.2025
 PDF print date: 28.02.2025
 Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
 400 ml Art.: 6210 2416, Art.: 6214 2416

Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	>= 1000	mg/kg	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), dermal:	NOAEL	>= 1000	mg/kg bw/d	Rabbit	OECD 410 (Repeated Dose Dermal Toxicity - 90-Day)	Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOEL	300	ppm	Rat	OECD 453 (Combined Chronic Toxicity/Carcinogenicity Studies)	Vapours, Analogous conclusion
Symptoms:						respiratory distress, drowsiness, unconsciousness, vomiting, headaches, mucous membrane irritation, dizziness, nausea

Ethanol						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	10470	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	51-124,7	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:				Mouse	OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:					OECD 475 (Mammalian Bone Marrow Chromosome Aberration Test)	Negative
Carcinogenicity:	NOAEL	>3000	mg/kg	Rat	OECD 451 (Carcinogenicity Studies)	24 mon
Reproductive toxicity:	NOAEL	5200	mg/kg bw/d	Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAL	>20	mg/l	Rat	OECD 403 (Acute Inhalation Toxicity)	Male
Specific target organ toxicity - repeated exposure (STOT-RE):	NOAEL	1730	mg/kg/d	Rat	OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Female

Page 18 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 28.02.2025 / 0025

Replacing version dated / version: 04.11.2024 / 0024

Valid from: 28.02.2025

PDF print date: 28.02.2025

Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222

400 ml Art.: 6210 2416, Art.: 6214 2416

Symptoms:						respiratory distress, drowsiness, unconsciousness, drop in blood pressure, vomiting, coughing, headaches, intoxication, drowsiness, mucous membrane irritation, dizziness, nausea
-----------	--	--	--	--	--	---

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter <= 10 µm)						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 425 (Acute Oral Toxicity - Up-and-Down Procedure)	
Acute toxicity, by dermal route:	LD50	>5000	mg/kg	Rabbit		
Acute toxicity, by inhalation:	LC50	>5,09-6,8	mg/l/4h	Rat		
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant, Mechanical irritation possible.
Respiratory or skin sensitisation:				Mouse	OECD 429 (Skin Sensitisation - Local Lymph Node Assay)	Not sensitising
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Mouse	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Germ cell mutagenicity:				Mammalian	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	(Ames-Test)	Negative
Germ cell mutagenicity:					OECD 476 (In Vitro Mammalian Cell Gene Mutation Test)	Negative
Germ cell mutagenicity:					OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	No indications of such an effect.
Specific target organ toxicity - single exposure (STOT-SE):						Not irritant (respiratory tract). (90d)
Specific target organ toxicity - repeated exposure (STOT-RE), oral:	NOAEL	3500	mg/kg/d	Rat		(90d)
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	10	mg/m3	Rat		(90d)

Page 19 of 33
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.02.2025 / 0025
 Replacing version dated / version: 04.11.2024 / 0024
 Valid from: 28.02.2025
 PDF print date: 28.02.2025
 Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
 400 ml Art.: 6210 2416, Art.: 6214 2416

Symptoms:						mucous membrane irritation, coughing, respiratory distress, drying of the skin.
-----------	--	--	--	--	--	---

Trizinc bis(orthophosphate)						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by inhalation:	LC50	>5,7	mg/l/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Analogous conclusion, Dust, Mist
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact), Analogous conclusion
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Germ cell mutagenicity:						Analogous conclusion, Negative
Carcinogenicity:						Analogous conclusion, Negative
Reproductive toxicity:						Analogous conclusion, Negative
Specific target organ toxicity - single exposure (STOT-SE):						Analogous conclusion, No
Specific target organ toxicity - single exposure (STOT-SE), inhalative:						Not irritant (respiratory tract), Analogous conclusion
Specific target organ toxicity - repeated exposure (STOT-RE):						Analogous conclusion, No
Symptoms:						breathing difficulties, fever, headaches, stomach pain, dizziness, nausea and vomiting.

Butane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Human being	OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative

Page 20 of 33
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.02.2025 / 0025
 Replacing version dated / version: 04.11.2024 / 0024
 Valid from: 28.02.2025
 PDF print date: 28.02.2025
 Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
 400 ml Art.: 6210 2416, Art.: 6214 2416

Germ cell mutagenicity:				Rat	OECD 474 (Mammalian Erythrocyte Micronucleus Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting.

Propane						
Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male, Analogous conclusion
Skin corrosion/irritation:						Not irritant
Serious eye damage/irritation:						Not irritant
Germ cell mutagenicity:					OECD 473 (In Vitro Mammalian Chromosome Aberration Test)	Negative
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Reproductive toxicity (Developmental toxicity):	NOAEC	21,641	mg/l		OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	7,214	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	LOAEL	21,641	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						breathing difficulties, unconsciousness, frostbite, headaches, cramps, mucous membrane irritation, dizziness, nausea and vomiting.

Isobutane

Page 21 of 33
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.02.2025 / 0025
 Replacing version dated / version: 04.11.2024 / 0024
 Valid from: 28.02.2025
 PDF print date: 28.02.2025
 Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
 400 ml Art.: 6210 2416, Art.: 6214 2416

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by inhalation:	LC50	658	mg/l/4h	Rat		
Acute toxicity, by inhalation:	LC50	260000	ppmV/4h	Rat		Gasses, Male
Serious eye damage/irritation:				Rabbit		Not irritant
Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEL	21,394	mg/l	Rat	OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Developm. Tox. Screening Test)	
Aspiration hazard:						No
Symptoms:						unconsciousness , frostbite, headaches, cramps, dizziness, nausea and vomiting.

11.2. Information on other hazards

Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
400 ml Art.: 6210 2416, Art.: 6214 2416

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.
Other information:						No other relevant information available on adverse effects on health.

Ethanol

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Other information:						Excessive alcohol consumption during pregnancy induces the foetus alcohol syndrome (reduced weight at birth, physical and mental disorders)., There is no sign that this syndrome is also caused by dermal or inhalative absorption., Experiences on persons.

Trizinc bis(orthophosphate)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						No

SECTION 12: Ecological information

Page 22 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 28.02.2025 / 0025

Replacing version dated / version: 04.11.2024 / 0024

Valid from: 28.02.2025

PDF print date: 28.02.2025

Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222

400 ml Art.: 6210 2416, Art.: 6214 2416

Possibly more information on environmental effects, see Section 2.1 (classification).

Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222

400 ml Art.: 6210 2416, Art.: 6214 2416

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							n.d.a.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:	AOX						According to the recipe, contains no AOX.
Other information:	DOC						DOC-elimination degree(complexing organic substance)>= 80%/28d: n.a.

Acetone

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	5540	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	7500	mg/l	Leuciscus idus		
12.1. Toxicity to fish:	LC50	96h	8300	mg/l	Lepomis macrochirus		
12.1. Toxicity to fish:	EC50	96h	8300	mg/l	Lepomis macrochirus		
12.1. Toxicity to daphnia:	NOEC/NOEL	28d	2212	mg/l	Daphnia pulex	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to daphnia:	EC50	48h	6100-12700	mg/l	Daphnia magna		
12.1. Toxicity to daphnia:	EC50	48h	8800	mg/l	Daphnia pulex	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	48h	4740	mg/l	Pseudokirchneriella subcapitata		
12.1. Toxicity to algae:	NOEC/NOEL	48h	3400	mg/l	Pseudokirchneriella subcapitata		
12.1. Toxicity to algae:	NOEC/NOEL	8d	530	mg/l		DIN 38412 T.9	Test organism: M. aeruginosa
12.2. Persistence and degradability:		30d	81-92	%		Regulation (EC) 440/2008 C.4-E (DETERMINATION OF 'READY' BIODEGRADABILITY - CLOSED BOTTLE TEST)	Readily biodegradable

Page 23 of 33
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.02.2025 / 0025
 Replacing version dated / version: 04.11.2024 / 0024
 Valid from: 28.02.2025
 PDF print date: 28.02.2025
 Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
 400 ml Art.: 6210 2416, Art.: 6214 2416

12.2. Persistence and degradability:		28d	91	%		OECD 301 A (Ready Biodegradability - DOC Die-Away Test)	Readily biodegradable
12.2. Persistence and degradability:		28d	91	%		OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-0,24			OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method)	
12.3. Bioaccumulative potential:	BCF		3				Low
12.4. Mobility in soil:							No adsorption in soil.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	30min	1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Toxicity to bacteria:	BOD/COD	16h	1700	mg/l	<i>Pseudomonas putida</i>		
Other organisms:	EC5	72h	28	mg/l	<i>Entosiphon sulcatum</i>		
Other information:	BOD5		1760-1900	mg/g			
Other information:	AOX		0	%			
Other information:	COD		2070-2100	mg/g			

Dimethyl ether

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC0	96h	2695	mg/l	<i>Pimephales promelas</i>		
12.1. Toxicity to fish:	LC50	96h	3082	mg/l	<i>Salmo gairdneri</i>		
12.1. Toxicity to fish:	LC50	96h	>4,1	mg/l	<i>Poecilia reticulata</i>		
12.1. Toxicity to daphnia:	EC50	48h	>4,4	mg/l	<i>Daphnia magna</i>		
12.1. Toxicity to algae:	EC50	96h	154,9	mg/l	<i>Chlorella vulgaris</i>		
12.2. Persistence and degradability:		28d	5	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Not readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		-0,07				Bioaccumulation is unlikely (LogPow < 1). 25°C (pH 7)
12.4. Mobility in soil:	H (Henry)		518,6	Pa*m3/mol			No adsorption in soil.
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10		>1600	mg/l	<i>Pseudomonas putida</i>		
Water solubility:			45,60	mg/l			25°C

n-butyl acetate

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	18	mg/l	Pimephales promelas	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	EC50	48h	44	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	21d	23	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	397	mg/l	Scenedesmus subspicatus	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	83	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		2,3			OECD 117 (Partition Coefficient (n-octanol/water) - HPLC method)	Low
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC50		356	mg/l			Tetrahymena pyriformis

Reaction mass of ethylbenzene and xylene

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	2,6	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	>3,4	mg/l	Ceriodaphnia spec.		
12.1. Toxicity to algae:	EC50	72h	1,3	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	Analogous conclusion
12.2. Persistence and degradability:		28d	90	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	BCF		25,9				Low, Analogous conclusion
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

2-methoxy-1-methylethyl acetate

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	100-180	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	14d	47,5	mg/l	Oryzias latipes	OECD 204 (Fish, Prolonged Toxicity Test - 14-Day Study)	
12.1. Toxicity to daphnia:	EC50	48h	373	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	

Page 25 of 33
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.02.2025 / 0025
 Replacing version dated / version: 04.11.2024 / 0024
 Valid from: 28.02.2025
 PDF print date: 28.02.2025
 Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
 400 ml Art.: 6210 2416, Art.: 6214 2416

12.1. Toxicity to daphnia:	NOEC/NOEL	21d	>100	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	
12.1. Toxicity to algae:	EC50	72h	>1000	mg/l	Selenastrum capricornutum	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	83-90	%	activated sludge	OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Kow		1,2			OECD 117 (Partition Coefficient (n-octanol/water) - HPLC method)	A notable biological accumulation potential is not to be expected (LogPow 1-3).20 °C, pH 6.8
12.4. Mobility in soil:	Koc		1,7-3,998				
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	EC10	30min	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:							Does not contain any organically bound halogens which can contribute to the AOX value in waste water.

Ethanol							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	13000	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	120h	250	mg/l	Brachydanio rerio	OECD 212 (Fish, Short-term Toxicity Test on Embryo and Sac-fry Stages)	
12.1. Toxicity to daphnia:	EC50	48h	5414	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	10d	9,6	mg/l	Ceriodaphnia spec.		References
12.1. Toxicity to algae:	EC50	72h	275	mg/l	Chlorella vulgaris	OECD 201 (Alga, Growth Inhibition Test)	
12.2. Persistence and degradability:		28d	97	%	activated sludge	OECD 301 B (Ready Biodegradability - Co2 Evolution Test)	Readily biodegradable
12.3. Bioaccumulative potential:	Log Pow		(-0,35) - (-0,32)				Bioaccumulation is unlikely (LogPow < 1).

Page 26 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 28.02.2025 / 0025

Replacing version dated / version: 04.11.2024 / 0024

Valid from: 28.02.2025

PDF print date: 28.02.2025

Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222

400 ml Art.: 6210 2416, Art.: 6214 2416

12.3. Bioaccumulative potential:	BCF		0,66 - 3,2				
12.4. Mobility in soil:	H (Henry)		0,000138				
12.4. Mobility in soil:	Koc		1,0				Highestimated
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
Toxicity to bacteria:	IC50	3h	>1000	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	Analogous conclusion
Other organisms:	NOEC/NOEL		280	mg/l	Lemna gibba	OECD 201 (Alga, Growth Inhibition Test)	
Other information:	COD		1,9	g/g			
Other information:	BOD5		1	g/g			

Titanium dioxide (in powder form containing 1 % or more of particles with aerodynamic diameter \leq 10 μ m)

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	>100	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to daphnia:	LC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	16	mg/l	Pseudokirchneriella subcapitata	U.S. EPA-600/9-78-018	
12.2. Persistence and degradability:							Not relevant for inorganic substances.
12.3. Bioaccumulative potential:	BCF	42d	9,6				Not to be expected
12.3. Bioaccumulative potential:	BCF	14d	19-352				Oncorhynchus mykiss
12.4. Mobility in soil:							Negative
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.6. Endocrine disrupting properties:							Negative
Toxicity to bacteria:			>5000	mg/l	Escherichia coli		
Toxicity to bacteria:	LC0	24h	>10000	mg/l	Pseudomonas fluorescens		
Toxicity to annelids:	NOEC/NOEL		>1000	mg/kg	Eisenia foetida		
Water solubility:							Insoluble20°C

Trizinc bis(orthophosphate)

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	0,09	mg/l	Oncorhynchus mykiss		
12.1. Toxicity to fish:	LC50	96h	0,177	mg/l	Oncorhynchus mykiss	U.S. EPA ECOTOX Database	
12.1. Toxicity to daphnia:	EC50	48h	28,2	mg/l	Daphnia magna		
12.1. Toxicity to algae:	ErC50	72h	11	mg/l	Desmodesmus subspicatus		
12.1. Toxicity to algae:	EC50	72h	0,136-0,15	mg/l	Selenastrum capricornutum		Analogous conclusion

Page 27 of 33
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.02.2025 / 0025
 Replacing version dated / version: 04.11.2024 / 0024
 Valid from: 28.02.2025
 PDF print date: 28.02.2025
 Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
 400 ml Art.: 6210 2416, Art.: 6214 2416

12.5. Results of PBT and vPvB assessment							Not relevant for inorganic substances.
12.6. Endocrine disrupting properties:							No
Toxicity to bacteria:	NOEC/NOEL	4h	0,1	mg/l	activated sludge		Analogous conclusion
Water solubility:							Insoluble Wasserlöslichkeit <0,1% (DIN ISO 787, Teil 3) bzw. 0,025 g Zn/l (67/548/EWG, Anh. V, C)

Butane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	24,11	mg/l		QSAR	
12.1. Toxicity to daphnia:	LC50	48h	14,22	mg/l		QSAR	
12.3. Bioaccumulative potential:	Log Pow		2,98				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.4. Mobility in soil:							Not to be expected
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Propane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.3. Bioaccumulative potential:	Log Pow		2,28				A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

Isobutane							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:	LC50	96h	27,98	mg/l			
12.1. Toxicity to algae:	EC50	96h	7,71	mg/l			
12.2. Persistence and degradability:							Readily biodegradable
12.3. Bioaccumulative potential:							A notable biological accumulation potential is not to be expected (LogPow 1-3).
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

Page 28 of 33
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.02.2025 / 0025
 Replacing version dated / version: 04.11.2024 / 0024
 Valid from: 28.02.2025
 PDF print date: 28.02.2025
 Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
 400 ml Art.: 6210 2416, Art.: 6214 2416

The waste codes are recommendations based on the scheduled use of this product.
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)
 08 01 11 waste paint and varnish containing organic solvents or other hazardous substances
 16 05 04 gases in pressure containers (including halons) containing hazardous substances
 Recommendation:
 Sewage disposal shall be discouraged.
 Pay attention to local and national official regulations.
 Take full aerosol cans to problem waste collection.
 Take emptied aerosol cans to valuable material collection.


For contaminated packing material

Pay attention to local and national official regulations.
 15 01 04 metallic packaging
 Recycling
 Do not perforate, cut up or weld uncleaned container.

SECTION 14: Transport information

General statements

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:		
UN 1950 AEROSOLS		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
14.5. Environmental hazards:	Not applicable	
Tunnel restriction code:	D	
Classification code:	5F	
LQ:	1 L	
Transport category:	2	

Transport by sea (IMDG-code)

14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:		
UN 1950 AEROSOLS		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
14.5. Environmental hazards:	Not applicable	
Marine Pollutant:	Not applicable	
EmS:	F-D, S-U	

Transport by air (IATA)

14.1. UN number or ID number:	1950	
14.2. UN proper shipping name:		
UN 1950 Aerosols, flammable		
14.3. Transport hazard class(es):	2.1	
14.4. Packing group:	-	
14.5. Environmental hazards:	Not applicable	

14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
 All persons involved in transporting must observe safety regulations.
 Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freight as packaged goods rather than in bulk, therefore not applicable.
 Minimum amount regulations have not been taken into account.
 Danger code and packing code on request.
 Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
 Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!

Page 29 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 28.02.2025 / 0025

Replacing version dated / version: 04.11.2024 / 0024

Valid from: 28.02.2025

PDF print date: 28.02.2025

Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222

400 ml Art.: 6210 2416, Art.: 6214 2416

This product is regulated by Regulation (EU) 2019/1148. All suspicious transactions, and significant disappearances and thefts should be reported to the relevant national contact point.

For exceptions see Regulation (EU) 2019/1148 and guidelines for the implementation of Regulation (EU) 2019/1148.

Comply with national regulations/laws governing maternity protection (national implementation of the Directive 92/85/EEC)!

Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

Hazard categories	Notes to Annex I	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements
P3a	11.1	150 (netto)	500 (netto)

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Entry Nr	Dangerous substances	Notes to Annex I	Qualifying quantity (tonnes) for the application of - Lower-tier requirements	Qualifying quantity (tonnes) for the application of - Upper-tier requirements
18	Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas	19	50	200

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 72,86 %

Observe incident regulations.

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections:

8

Employee training in handling dangerous goods is required.

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Eye Irrit. 2, H319	Classification according to calculation procedure.
STOT SE 3, H336	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.
Aerosol 1, H222	Classification according to calculation procedure.
Aerosol 1, H229	Classification based on the form or physical state.

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H351 Suspected of causing cancer by inhalation.

H304 May be fatal if swallowed and enters airways.

Page 30 of 33
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
Revision date / version: 28.02.2025 / 0025
Replacing version dated / version: 04.11.2024 / 0024
Valid from: 28.02.2025
PDF print date: 28.02.2025
Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
400 ml Art.: 6210 2416, Art.: 6214 2416

H312 Harmful in contact with skin.
H315 Causes skin irritation.
H318 Causes serious eye damage.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H373 May cause damage to organs through prolonged or repeated exposure.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H220 Extremely flammable gas.
EUH066 Repeated exposure may cause skin dryness or cracking.

Eye Irrit. — Eye irritation
STOT SE — Specific target organ toxicity - single exposure - narcotic effects
Aquatic Chronic — Hazardous to the aquatic environment - chronic
Aerosol — Aerosols
Flam. Liq. — Flammable liquid
Flam. Gas — Flammable gases - Flammable gas
Acute Tox. — Acute toxicity - dermal
Acute Tox. — Acute toxicity - inhalation
Skin Irrit. — Skin irritation
STOT SE — Specific target organ toxicity - single exposure - respiratory tract irritation
STOT RE — Specific target organ toxicity - repeated exposure
Asp. Tox. — Aspiration hazard
Carc. — Carcinogenicity
Aquatic Acute — Hazardous to the aquatic environment - acute
Eye Dam. — Serious eye damage

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
Guidelines for the preparation of safety data sheets as amended (ECHA).
Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
Safety data sheets for the constituent substances.
ECHA Homepage - Information about chemicals.
GESTIS Substance Database (Germany).
German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
National Lists of Occupational Exposure Limits for each country as amended.
Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Förch SAS
ZAE Le Marchais Renard
77950 Montereau-sur-le-Jard
Frankreich
Tel. +33 1 64 14 48 48
Fax. +33 1 64 14 48 49
E-Mail: info@forch.fr
Internet: www.forch.fr

FÖRCH S.R.L.
STR. ECOLOGISTILOR 43
RO - 505600 SACELE, JUD.BRASOV
Rumänien
Tel. +40 368 408192
Fax. +40 368 408193
E-Mail: info@foerch.ro
Internet: www.foerch.ro

Foerch AG
Muttenerstrasse 143
4133 Pratteln
Schweiz
Tel. +41 61 826 20 31
Fax. +41 61 8262039
E-Mail: info@foerch.ch
Internet: www.foerch.ch

Foerch Bulgaria EOOD
2 Novoto livade Str.
Kremikovtzi district
1839 Sofia
Bulgaria
foerch.bg

Förch d.o.o.
Buzinska cesta 58
10010 Zagreb
Kroatien
Tel. +385 1 2912900
Fax. +385 1 2912901
E-Mail: info@foerch.hr
internet: www.foerch.hr

Theo Förch GmbH
Röcklbrunnstraße 39A
5020 Salzburg
Österreich
Tel. +43 662 875574-0
Fax +43 662 878677-21
Verkauf Tel. +43 662 875574-900
Verkauf Fax +43 662 875574-30
E-Mail: info@foerch.at
Internet: www.foerch.at

Page 31 of 33
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
Revision date / version: 28.02.2025 / 0025
Replacing version dated / version: 04.11.2024 / 0024
Valid from: 28.02.2025
PDF print date: 28.02.2025
Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
400 ml Art.: 6210 2416, Art.: 6214 2416

Förch Componentes para Taller S.L.
CITAI - Avda. de la Serrezuela, 24
18130 - Escúzar (Granada)
Tel. +34 958 401 776
Fax. +34 958 401 787
E-Mail: info@forch.es
Internet: www.forch.es

Förch A/S
Hagemannsvej 3
8600 Silkeborg
Dänemark
Tel. +45 86 823711
Fax. +45 86 800617
E-Mail: info@foerch.dk
Internet: www.foerch.dk

FÖRCH Belux I Lhomme Tools
Mondeolaan 2A0001
3600 Genk
Tel: +32 89 71 66 61
E-Mail: info@foerch.be

Ziebe Limited
7 Century Court, Westcott, Venture Park
Aylesbury, Bucks, HP18 0XP (UK)
Great Britain
Tel +44 12 96 65 52 82
E-Mail: sales@ziebe.co.uk
Internet: www.ziebe.co.uk

Vardalis SM P.C.
Ethnikis Antistasis 62
57007 Chalkidona-Thessaloniki
Griechenland
Tel. +30 23910 21222
Fax. +30 23910 21223
E-Mail: info@forch.gr
Internet: www.forch.gr

Förch Kereskedelmi Kft
Börgöndi út 14
8000 Székesfehérvár
Ungarn
Tel. +36 22 348348
Fax. +36 22 348355
E-Mail: info@foerch.hu
Internet: www.foerch.hu

Förch S.r.l.
Via Antonio Stradivari 4
39100 Bolzano (BZ)
Italien
Tel: +39 0471 204330
Fax: +39 0471 204290
E-Mail: info@forch.it
Internet: www.forch.it

Förch Nederland BV
Twentepoort Oost 51
7609 RG Almelo
Niederlande
Tel. +31 85 77 32 420
E-Mail: info@foerch.nl
Internet: www.foerch.nl

AB varahlutir ehf
Funahöfði 9
110 Reykjavík
Tel. +354 567 6020
E-mail: ab@ab.is
Internet: www.ab.is

Förch Slovensko s.r.o.
Rosinská cesta 8
010 08 Žilina
Slowakei
Tel +421 41 5002454
E-Mail: info@forch.sk
Internet: www.forch.sk

Förch Sverige AB
Brännarevägen 1
151 55 Södertälje
Schweden
Tel. +46 855089264
E-mail: info@foerch.se
Internet: www.foerch.se

Förch, s.r.o.
Dopravní 1314/1
104 00 Praha 10 – Uhřetěves
Tschechien
Tel. +420 271 001 986-9
E-Mail: info@foerch.cz
Internet: www.foerch.cz

FORCH d.o.o.
Ljubljanska cesta 51A
1236 Trzin
Slowenien
Tel. +386 1 2442490
Fax. +386 1 2442492
E-Mail: info@foerch.si
Internet: www.foerch.si

Forch Australia
2 Forward Street
Gnangara WA 6077
Tel. +61 (08) 9303 9113
Fax. +61 (08) 9303 9114
Emergency telephone: +614 24 024 982
Email : sales@forch.com.au
Internet: www.forch.com.au

Troscoe Ltd
2D Lorient Place
East Tamaki 2013, New Zealand
Tel: +64 21 081 30780 / +64 21 024 05583
Email:sales@forchnz.co.nz
Internet: www.forchnz.co.nz

Förch Portugal Lda
Centro Empresarial Sintra-Estoril III
Rua Pé de Mouro, Nº 33, Armazém J
2710-335 Sintra
Portugal
Tel. +351 21 162 20 00
E-Mail: info@forch.pt
Internet: www.forch.pt

Trigers SIA
Straupes iela 3
1073 Rīga
Lettland
Tel. +371 6 7 90 25 15
Fax. +371 67 90 24 96
E-Mail: trigers@trigers.lv
Internet: www.trigers.lv

Förch Otom.İns.ve San.Ürün.Paz.Ltd.Şti.
Haramidere Mevkii Beysan Sanayi
Sitesi Birlik Caddesi No:6/3
34524 Beylikdüzü / İstanbul
Türkei
Tel. +90 (0)212 422 8744-45
Fax. +90 (0)212 422 8788
E-Mail: info@forch.com.tr
Internet: www.forch.com.tr

Page 32 of 33
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)
 Revision date / version: 28.02.2025 / 0025
 Replacing version dated / version: 04.11.2024 / 0024
 Valid from: 28.02.2025
 PDF print date: 28.02.2025
 Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222
 400 ml Art.: 6210 2416, Art.: 6214 2416

Total Consumables Ltd
 Coolnafearagh
 Monasterevin
 Co. Kildare
 W34 TX29
 Irland
 Tel. +353871271473

Venus Arma d.o.o.
 Partner Theo Förch GmbH & Co. KG
 Batajnicki drum 18a
 11080 Beograd Zemun
 Republika Srbija
 Tel. +381 11 4072 082
 Fax. +381 11 4072 091
 E-Mail: office@foerch.rs
 Internet: www.foerch.rs

Förch Polska Sp. z o.o.
 43-392 Miedzyrzeczce Górne 379
 k/Bielska-Bialej
 Tel.: +48 33 8196000
 Fax: +48 33 8158548
 E-Mail: info@forch.pl
 Internet: www.forch.pl

Förch Norge AS
 Østre Blixrudvei 4
 1940 Bjørkelangen
 Norwegen
 Telefon: +47 63 85 43 20
 Mail: info@foerch.no
 Internet: www.foerch.no

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ASTM ASTM International (American Society for Testing and Materials)
 ATE Acute Toxicity Estimate
 BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BSEF The International Bromine Council
 CAS Chemical Abstracts Service
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
 EC European Community
 ECHA European Chemicals Agency
 ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ErCx, ErCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
 etc. et cetera
 EU European Union
 EVAL Ethylene-vinyl alcohol copolymer
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 Koc Adsorption coefficient of organic carbon in the soil
 Kow octanol-water partition coefficient
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC (Code) International Bulk Chemical (Code)

Page 33 of 33

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II (last amended by Regulation (EU) 2020/878)

Revision date / version: 28.02.2025 / 0025

Replacing version dated / version: 04.11.2024 / 0024

Valid from: 28.02.2025

PDF print date: 28.02.2025

Thick Film Lacquer 4-in-1 Graphite black RAL 9011 L222

400 ml Art.: 6210 2416, Art.: 6214 2416

IMDG-code International Maritime Code for Dangerous Goods
incl. including, inclusive
IUCID International Uniform Chemical Information Database
IUPAC International Union for Pure Applied Chemistry
LC50 Lethal Concentration to 50 % of a test population
LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
Log Kow, Log Pow Logarithm of octanol-water partition coefficient
LQ Limited Quantities
MARPOL International Convention for the Prevention of Marine Pollution from Ships
mg/kg bw mg/kg body weight
mg/kg bw/d, mg/kg bw/day mg/kg body weight/day
mg/kg dw mg/kg dry weight
mg/kg wwt mg/kg wet weight
n.a. not applicable
n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute for Occupational Safety and Health (USA)
NLP No-longer-Polymer
NOEC, NOEL No Observed Effect Concentration/Level
OECD Organisation for Economic Co-operation and Development
org. organic
OSHA Occupational Safety and Health Administration (USA)
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
TOC Total organic carbon
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.