

Page 1 of 17  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0015  
Replacing version dated / version: 09.10.2018 / 0014  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
Engine Flush'n'Clean  
300 ml Art.: 6750 7030, Art.: 6754 7030

## Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1 Product identifier

**Engine Flush'n'Clean**  
**300 ml Art.: 6750 7030, Art.: 6754 7030**

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

##### Relevant identified uses of the substance or mixture:

Cleaner

See definition of the substance or mixture.

##### Uses advised against:

No information available at present.

#### 1.3 Details of the supplier of the safety data sheet

Theo Förch GmbH & Co. KG  
Theo-Förch-Str. 11 – 15  
74196 Neuenstadt  
Tel.: 07139/95-0  
Fax: 07139/95-199  
Email: [info@foerch.de](mailto:info@foerch.de)  
Homepage: [www.foerch.com](http://www.foerch.com)

Details of the supplier of the safety data sheet see section 16 of this safety data sheet.

Qualified person's e-mail address: [info@chemical-check.de](mailto:info@chemical-check.de), [k.schnurbusch@chemical-check.de](mailto:k.schnurbusch@chemical-check.de) Please DO NOT use for requesting Safety Data Sheets.

#### 1.4 Emergency telephone number

##### Emergency information services / official advisory body:

---

##### Telephone number of the company in case of emergencies:

+49 (0) 700 / 24 112 112 (TFC)

### SECTION 2: Hazards identification

#### 2.1 Classification of the substance or mixture

##### Classification according to Regulation (EC) 1272/2008 (CLP)

Hazard class	Hazard category	Hazard statement
Asp. Tox.	1	H304-May be fatal if swallowed and enters airways.
Aquatic Chronic	3	H412-Harmful to aquatic life with long lasting effects.

#### 2.2 Label elements

##### Labeling according to Regulation (EC) 1272/2008 (CLP)

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0015  
 Replacing version dated / version: 09.10.2018 / 0014  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Engine Flush'n'Clean  
 300 ml Art.: 6750 7030, Art.: 6754 7030



Danger

H304-May be fatal if swallowed and enters airways. H412-Harmful to aquatic life with long lasting effects.

P273-Avoid release to the environment.

P301+P310-IF SWALLOWED: Immediately call a POISON CENTER / doctor. P331-Do NOT induce vomiting.

EUH066-Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C10, aromatics, <1% naphthalene  
 C8-C26 branched and linear hydrocarbons - Distillates

### 2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

## SECTION 3: Composition/information on ingredients

### 3.1 Substances

n.a.

### 3.2 Mixtures

C8-C26 branched and linear hydrocarbons - Distillates	
Registration number (REACH)	01-0000020119-75-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	481-740-5
CAS	848301-67-7
content %	50-<70
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 Asp. Tox. 1, H304

Hydrocarbons, C10, aromatics, <1% naphthalene	
Registration number (REACH)	01-2119463583-34-XXXX
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	918-811-1
CAS	(64742-94-5)
content %	10-<20
Classification according to Regulation (EC) 1272/2008 (CLP), M-factors	EUH066 STOT SE 3, H336 Asp. Tox. 1, H304 Aquatic Chronic 2, H411

Amides, C16-18 and C18-unsatd., N,N-bis(hydroxyethyl)	
Registration number (REACH)	---
Index	---
EINECS, ELINCS, NLP, REACH-IT List-No.	271-653-9
CAS	68603-38-3
content %	1-<5

GB

Page 3 of 17  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0015  
Replacing version dated / version: 09.10.2018 / 0014  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
Engine Flush'n'Clean  
300 ml Art.: 6750 7030, Art.: 6754 7030

**Classification according to Regulation (EC) 1272/2008 (CLP), M-factors**

Skin Irrit. 2, H315  
Eye Irrit. 2, H319  
Aquatic Chronic 2, H411

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.  
The substances named in this section are given with their actual, appropriate classification!  
For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

**SECTION 4: First aid measures****4.1 Description of first aid measures**

First-aiders should ensure they are protected!  
Never pour anything into the mouth of an unconscious person!

**Inhalation**

Remove person from danger area.  
Supply person with fresh air and consult doctor according to symptoms.  
If the person is unconscious, place in a stable side position and consult a doctor.

**Skin contact**

Wash thoroughly using copious water - remove contaminated clothing immediately. If skin irritation occurs (redness etc.), consult doctor.

**Eye contact**

Remove contact lenses.  
Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

**Ingestion**

Rinse the mouth thoroughly with water.  
Do not induce vomiting. Consult doctor immediately.  
Danger of aspiration.  
In case of vomiting, keep head low so that the stomach content does not reach the lungs.  
Immediate admittance to a hospital.

**4.2 Most important symptoms and effects, both acute and delayed**

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

The following may occur:

Irritation of the eyes  
Irritation of the respiratory tract  
Nausea  
Dizziness  
Effects/damages the central nervous system  
Unconsciousness  
with long-term contact:  
Product removes fat.  
Drying of the skin.  
Dermatitis (skin inflammation)

Ingestion:

Lung damage  
Oedema of the lungs  
Chemical pneumonitis (condition similar to pneumonia)  
In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

**4.3 Indication of any immediate medical attention and special treatment needed**

Ingestion:

Activated carbon  
Gastric lavage (stomach washing) only under endotracheal intubation.  
Subsequent observation for pneumonia and pulmonary oedema.

**SECTION 5: Firefighting measures****5.1 Extinguishing media****Suitable extinguishing media**

Water jet spray / alcohol resistant foam / CO<sub>2</sub> / dry extinguisher.

**Unsuitable extinguishing media**

High volume water jet

**5.2 Special hazards arising from the substance or mixture**

GB

Page 4 of 17  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0015  
Replacing version dated / version: 09.10.2018 / 0014  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
Engine Flush'n'Clean  
300 ml Art.: 6750 7030, Art.: 6754 7030

In case of fire the following can develop:

Oxides of carbon  
Toxic gases  
Flammable vapour/air mixtures

### 5.3 Advice for firefighters

For personal protective equipment see Section 8.  
In case of fire and/or explosion do not breathe fumes.  
Protective respirator with independent air supply.  
According to size of fire  
Full protection, if necessary.  
Cool container at risk with water.  
Dispose of contaminated extinction water according to official regulations.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

#### 6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination.  
Ensure sufficient ventilation, remove sources of ignition.  
Avoid dust formation with solid or powder products.  
Leave the danger zone if possible, use existing emergency plans if necessary.  
Remove possible causes of ignition - do not smoke.  
Ensure sufficient supply of air.  
Avoid inhalation, and contact with eyes or skin.  
If applicable, caution - risk of slipping.

#### 6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

### 6.2 Environmental precautions

If leakage occurs, dam up.  
Resolve leaks if this possible without risk.  
Prevent surface and ground-water infiltration, as well as ground penetration.  
Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous.  
If accidental entry into drainage system occurs, inform responsible authorities.

### 6.3 Methods and material for containment and cleaning up

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.  
Fill the absorbed material into lockable containers.

### 6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

## SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

### 7.1 Precautions for safe handling

#### 7.1.1 General recommendations

Ensure good ventilation.  
Avoid inhalation of the vapours.  
Avoid contact with eyes or skin.  
Keep away from sources of ignition - Do not smoke.  
Eating, drinking, smoking, as well as food-storage, is prohibited in work-room.  
Observe directions on label and instructions for use.  
Use working methods according to operating instructions.

#### 7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable.  
Wash hands before breaks and at end of work.  
Keep away from food, drink and animal feedingstuffs.  
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

### 7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals.  
Store product closed and only in original packing.  
Not to be stored in gangways or stair wells.  
Store in a well-ventilated place.

GB

Page 5 of 17  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0015  
 Replacing version dated / version: 09.10.2018 / 0014  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Engine Flush'n'Clean  
 300 ml Art.: 6750 7030, Art.: 6754 7030

Store cool.

### 7.3 Specific end use(s)

No information available at present.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

Workplace exposure limit (WEL) of the total hydrocarbon solvent content of the mixture (RCP method according to EH40):  
 1000 mg/m<sup>3</sup>

GB	Chemical Name	C8-C26 branched and linear hydrocarbons - Distillates
	WEL-TWA: 1200 mg/m <sup>3</sup> (>=C7 normal and branched chain alkanes)	WEL-STEL: ---
	Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174)
	BMGV: ---	Other information: ---
GB	Chemical Name	Hydrocarbons, C10, aromatics, <1% naphthalene
	WEL-TWA: 500 mg/m <sup>3</sup> (Aromatics)	WEL-STEL: ---
	Monitoring procedures:	- Draeger - Hydrocarbons 0,1%/c (81 03 571) - Draeger - Hydrocarbons 2/a (81 03 581) - Compur - KITA-187 S (551 174)
	BMGV: ---	Other information: ---
GB	Chemical Name	Oil mist, mineral
	WEL-TWA: 5 mg/m <sup>3</sup> (Mineral oil, excluding metal working fluids, ACGIH)	WEL-STEL: ---
	Monitoring procedures:	- Draeger - Oil Mist 1/a (67 33 031)
	BMGV: ---	Other information: ---

Hydrocarbons, C10, aromatics, <1% naphthalene						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
Consumer	Human - dermal	Long term	DNEL	7,5	mg/kg bw/day	
Consumer	Human - inhalation	Long term	DNEL	32	mg/m <sup>3</sup>	
Consumer	Human - oral	Long term	DNEL	7,5	mg/kg bw/day	
Workers / employees	Human - dermal	Long term	DNEL	12,5	mg/kg bw/day	
Workers / employees	Human - inhalation	Long term	DNEL	151	mg/m <sup>3</sup>	

Amides, C16-18 and C18-unsatd., N,N-bis(hydroxyethyl)						
Area of application	Exposure route / Environmental compartment	Effect on health	Descriptor	Value	Unit	Note
	Environment - freshwater		PNEC	7	µg/l	
	Environment - marine		PNEC	0,7	µg/l	
	Environment - sewage treatment plant		PNEC	830	mg/l	
	Environment - sediment, freshwater		PNEC	211,15	µg/l	
	Environment - soil		PNEC	0,09979	mg/kg dw	
Consumer	Human - inhalation	Long term, systemic effects	DNEL	21,73	mg/m <sup>3</sup>	
Consumer	Human - dermal	Long term, systemic effects	DNEL	2,5	mg/kg bw/d	
Consumer	Human - dermal	Long term, local effects	DNEL	0,0562	mg/cm <sup>2</sup>	
Consumer	Human - oral	Long term, systemic effects	DNEL	6,25	mg/kg bw/d	

Ⓢ

Page 6 of 17  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0015  
 Replacing version dated / version: 09.10.2018 / 0014  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Engine Flush'n'Clean  
 300 ml Art.: 6750 7030, Art.: 6754 7030

Workers / employees	Human - inhalation	Long term, systemic effects	DNEL	73,44	mg/m3	
Workers / employees	Human - dermal	Long term, systemic effects	DNEL	4,16	mg/kg bw/d	
Workers / employees	Human - dermal	Long term, local effects	DNEL	0,0936	mg/cm2	

Ⓢ WEL-TWA = Workplace Exposure Limit - Long-term exposure limit (8-hour TWA (= time weighted average) reference period) EH40. AGW = "Arbeitsplatzgrenzwert" (workplace limit value, Germany).  
 (8) = Inhalable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (9) = Respirable fraction (Directive 2017/164/EU, Directive 2004/37/CE). (11) = Inhalable fraction (Directive 2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (Directive 2004/37/CE). | WEL-STEL = Workplace Exposure Limit - Short-term exposure limit (15-minute reference period).  
 (8) = Inhalable fraction (2017/164/EU, 2017/2398/EU). (9) = Respirable fraction (2017/164/EU, 2017/2398/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). | BMGV = Biological monitoring guidance value EH40. BGW = "Biologischer Grenzwert" (biological limit value, Germany) | Other information: Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.  
 \*\* = The exposure limit for this substance is repealed through the TRGS 900 (Germany) of January 2006 with the goal of revision.  
 (13) = The substance can cause sensitisation of the skin and of the respiratory tract (Directive 2004/37/CE), (14) = The substance can cause sensitisation of the skin (Directive 2004/37/CE).

## 8.2 Exposure controls

### 8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.  
 If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.  
 Applies only if maximum permissible exposure values are listed here.  
 Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.  
 These are specified by e.g. EN 14042.  
 EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

### 8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.  
 Wash hands before breaks and at end of work.  
 Keep away from food, drink and animal feedingstuffs.  
 Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:  
 Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:  
 Solvent resistant protective gloves (EN ISO 374).  
 Recommended  
 Protective nitrile gloves (EN ISO 374).  
 Protective Neoprene® / polychloroprene gloves (EN ISO 374).  
 Minimum layer thickness in mm:  
 > 0,1  
 Permeation time (penetration time) in minutes:  
 > 30  
 Protective hand cream recommended.  
 The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.  
 The recommended maximum wearing time is 50% of breakthrough time.

Skin protection - Other:  
 Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:  
 If OES or MEL is exceeded.  
 Filter A (EN 14387), code colour brown  
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:  
 Not applicable

Additional information on hand protection - No tests have been performed.

Page 7 of 17  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0015  
Replacing version dated / version: 09.10.2018 / 0014  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
Engine Flush'n'Clean  
300 ml Art.: 6750 7030, Art.: 6754 7030

In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.  
Selection of materials derived from glove manufacturer's indications.  
Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.  
Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.  
In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.  
The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

### 8.2.3 Environmental exposure controls

No information available at present.

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

Physical state:	Liquid
Colour:	Yellow
Odour:	Characteristic
Melting point/freezing point:	There is no information available on this parameter.
Boiling point or initial boiling point and boiling range:	There is no information available on this parameter.
Flammability:	No
Lower explosion limit:	There is no information available on this parameter.
Upper explosion limit:	There is no information available on this parameter.
Flash point:	72°C
Auto-ignition temperature:	There is no information available on this parameter.
Decomposition temperature:	There is no information available on this parameter.
pH:	There is no information available on this parameter.
Kinematic viscosity:	<=20,5 mm <sup>2</sup> /s (40°C)
Kinematic viscosity:	3,6 mm <sup>2</sup> /s (40°C)
Solubility:	There is no information available on this parameter.
Partition coefficient n-octanol/water (log value):	Does not apply to mixtures.
Vapour pressure:	There is no information available on this parameter.
Density and/or relative density:	826 kg/m <sup>3</sup> (20°C)
Relative vapour density:	There is no information available on this parameter.
Particle characteristics:	Does not apply to liquids.

### 9.2 Other information

Explosives:	Product is not explosive.
Oxidising liquids:	There is no information available on this parameter.
Solvents content:	71,6 % (Organic solvents )

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

The product has not been tested.

### 10.2 Chemical stability

Stable with proper storage and handling.

### 10.3 Possibility of hazardous reactions

No dangerous reactions are known.

### 10.4 Conditions to avoid

See also section 7.

Heating, open flame, ignition sources

### 10.5 Incompatible materials

See also section 7.

Avoid contact with strong oxidizing agents.

Avoid contact with strong acids.

### 10.6 Hazardous decomposition products

See also section 5.2

No decomposition when used as directed.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

GB

Page 8 of 17  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0015  
 Replacing version dated / version: 09.10.2018 / 0014  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Engine Flush'n'Clean  
 300 ml Art.: 6750 7030, Art.: 6754 7030

Possibly more information on health effects, see Section 2.1 (classification).

**Engine Flush'n'Clean**

**300 ml Art.: 6750 7030, Art.: 6754 7030**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:						n.d.a.
Acute toxicity, by dermal route:						n.d.a.
Acute toxicity, by inhalation:						n.d.a.
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:						n.d.a.
Respiratory or skin sensitisation:						n.d.a.
Germ cell mutagenicity:						n.d.a.
Carcinogenicity:						n.d.a.
Reproductive toxicity:						n.d.a.
Specific target organ toxicity - single exposure (STOT-SE):						n.d.a.
Specific target organ toxicity - repeated exposure (STOT-RE):						n.d.a.
Aspiration hazard:						n.d.a.
Symptoms:						n.d.a.

**C8-C26 branched and linear hydrocarbons - Distillates**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 420 (Acute Oral Toxicity - Fixe Dose Procedure)	Analogous conclusion
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rat	Regulation (EC) 440/2008 B.3 (ACUTE TOXICITY (DERMAL))	Analogous conclusion
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Aspiration hazard:						Yes

**Hydrocarbons, C10, aromatics, <1% naphthalene**

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>5000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit	OECD 402 (Acute Dermal Toxicity)	
Acute toxicity, by inhalation:	LC50	>4688	mg/m3/4h	Rat	OECD 403 (Acute Inhalation Toxicity)	Vapours
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Not irritant
Skin corrosion/irritation:						Repeated exposure may cause skin dryness or cracking.
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Not irritant
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	Not sensitizing
Germ cell mutagenicity:					OECD 479 (Genetic Toxicology - In Vitro Sister Chromatid Exchange assay in Mammalian Cells)	Negative

Page 9 of 17  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0015  
 Replacing version dated / version: 09.10.2018 / 0014  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Engine Flush'n'Clean  
 300 ml Art.: 6750 7030, Art.: 6754 7030

Germ cell mutagenicity:				Salmonella typhimurium	OECD 471 (Bacterial Reverse Mutation Test)	Negative, Analogous conclusion
Reproductive toxicity (Developmental toxicity):				Rat	OECD 414 (Prenatal Developmental Toxicity Study)	Negative, Analogous conclusion oral
Reproductive toxicity (Effects on fertility):				Rat	OECD 416 (Two-generation Reproduction Toxicity Study)	Negative, Analogous conclusion inhalat iv
Specific target organ toxicity - single exposure (STOT-SE):						May cause drowsiness or dizziness., STOT SE 3, H336
Specific target organ toxicity - repeated exposure (STOT-RE):					OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)	Negative
Aspiration hazard:						Yes
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	>0,38	mg/l	Rat	OECD 413 (Subchronic Inhalation Toxicity - 90-Day Study)	Vapours, Analogous conclusion 13 weeks
Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.:	NOAEC	900	mg/m3	Rat	OECD 452 (Chronic Toxicity Studies)	Vapours, Analogous conclusion 12 months
Symptoms:						headaches, dizziness, fatigue, nausea and vomiting.
Symptoms:						drowsiness, headaches, drowsiness, dizziness

#### Amides, C16-18 and C18-unsatd., N,N-bis(hydroxyethyl)

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Acute toxicity, by oral route:	LD50	>3000	mg/kg	Rat	OECD 401 (Acute Oral Toxicity)	
Acute toxicity, by dermal route:	LD50	>2000	mg/kg	Rabbit		Analogous conclusion
Skin corrosion/irritation:				Rabbit	OECD 404 (Acute Dermal Irritation/Corrosion)	Skin Irrit. 2
Serious eye damage/irritation:				Rabbit	OECD 405 (Acute Eye Irritation/Corrosion)	Eye Irrit. 2
Respiratory or skin sensitisation:				Guinea pig	OECD 406 (Skin Sensitisation)	No (skin contact)
Germ cell mutagenicity:				Salmonella typhimurium	Regulation (EC) 440/2008 B.13/B.14 (REVERSE MUTATION TEST USING BACTERIA)	Negative
Reproductive toxicity:	NOAEL	>1000	mg/kg bw/d	Rat	OECD 414 (Prenatal Developmental Toxicity Study)	

## 11.2. Information on other hazards

Engine Flush'n'Clean  
 300 ml Art.: 6750 7030, Art.: 6754 7030

Toxicity / effect	Endpoint	Value	Unit	Organism	Test method	Notes
Endocrine disrupting properties:						Does not apply to mixtures.

GB

Page 10 of 17  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0015  
 Replacing version dated / version: 09.10.2018 / 0014  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Engine Flush'n'Clean  
 300 ml Art.: 6750 7030, Art.: 6754 7030

Other information:							No other relevant information available on adverse effects on health.
--------------------	--	--	--	--	--	--	---

**SECTION 12: Ecological information**

Possibly more information on environmental effects, see Section 2.1 (classification).

Engine Flush'n'Clean 300 ml Art.: 6750 7030, Art.: 6754 7030							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.1. Toxicity to fish:							n.d.a.
12.1. Toxicity to daphnia:							n.d.a.
12.1. Toxicity to algae:							n.d.a.
12.2. Persistence and degradability:							The surfactant(s) contained in this mixture complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Supporting documents that confirm this are kept available for the competent authorities and will be provided by a detergent manufacturer upon inquiry or demand. Isolate as much as possible with an oil separator.
12.3. Bioaccumulative potential:							n.d.a.
12.4. Mobility in soil:							n.d.a.
12.5. Results of PBT and vPvB assessment							n.d.a.
12.6. Endocrine disrupting properties:							Does not apply to mixtures.
12.7. Other adverse effects:							No information available on other adverse effects on the environment.
Other information:	AOX						According to the recipe, contains no AOX.
Other information:							DOC-elimination degree(complexing organic substance)>= 80%/28d: n.a.

C8-C26 branched and linear hydrocarbons - Distillates							
Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes

12.2. Persistence and degradability:		28d	68	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Readily biodegradable
12.1. Toxicity to fish:	LC50	96h	>1000	mg/l	Pimephales promelas	Regulation (EC) 440/2008 C.1 (ACUTE TOXICITY FOR FISH)	
12.1. Toxicity to fish:	NOEC/NOEL		>100	mg/l			
12.1. Toxicity to daphnia:	EC50	48h	>100	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to daphnia:	NOEC/NOEL	48h	>1000	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	
12.1. Toxicity to algae:	EC50	72h	>100	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
Toxicity to bacteria:	EC50	3h	>100	mg/l	activated sludge	OECD 209 (Activated Sludge, Respiration Inhibition Test (Carbon and Ammonium Oxidation))	
Other information:	Log Pow		>6,5				
Water solubility:							Insoluble, Product floats on the water surface.

**Hydrocarbons, C10, aromatics, <1% naphthalene**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.5. Results of PBT and vPvB assessment							No PBT substance, No vPvB substance
12.1. Toxicity to fish:	LC50	96h	2-5	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LL50	96h	2 - 5	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	LL50	96h	2-5	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	3 -10	mg/l	Daphnia magna	OECD 202 (Daphnia sp. Acute Immobilisation Test)	Analogous conclusion
12.1. Toxicity to algae:	NOELR	72h	2,5	mg/l	Pseudokirchneriella subcapitata	OECD 201 (Alga, Growth Inhibition Test)	
12.1. Toxicity to algae:	EC50	72h	>1 -3	mg/l	Raphidocelis subcapitata	OECD 201 (Alga, Growth Inhibition Test)	

GB

Page 12 of 17  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0015  
 Replacing version dated / version: 09.10.2018 / 0014  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Engine Flush'n'Clean  
 300 ml Art.: 6750 7030, Art.: 6754 7030

12.2. Persistence and degradability:		28d	49,6	%		OECD 301 F (Ready Biodegradability - Manometric Respirometry Test)	Not readily but inherent biodegradable., Inherent
12.3. Bioaccumulative potential:	BCF		<100				Low
Water solubility:							Insoluble

**Amides, C16-18 and C18-unsatd., N,N-bis(hydroxyethyl)**

Toxicity / effect	Endpoint	Time	Value	Unit	Organism	Test method	Notes
12.2. Persistence and degradability:		28d	60	%		OECD 301 D (Ready Biodegradability - Closed Bottle Test)	
12.1. Toxicity to fish:	LC50	96h	1,2	mg/l	Oncorhynchus mykiss	OECD 203 (Fish, Acute Toxicity Test)	
12.1. Toxicity to fish:	NOEC/NOEL	28d	0,32	mg/l	Oncorhynchus mykiss	OECD 204 (Fish, Prolonged Toxicity Test - 14-Day Study)	Analogous conclusion
12.1. Toxicity to daphnia:	LOEC/LOEL	21d	0,24	mg/l	Daphnia magna	OECD 211 (Daphnia magna Reproduction Test)	Analogous conclusion
12.1. Toxicity to daphnia:	EC50	48h	0,9	mg/l	Daphnia magna	Regulation (EC) 440/2008 C.2 (DAPHNIA SP. ACUTE IMMOBILISATION TEST)	
12.1. Toxicity to algae:	EC50	72h	18,6	mg/l	Desmodesmus subspicatus	Regulation (EC) 440/2008 C.3 (FRESHWATER ALGAE AND CYANOBACTERIA, GROWTH INHIBITION TEST)	
Toxicity to bacteria:	EC50	72h	6	mg/l	Pseudomonas putida	DIN 38412 T.8	Analogous conclusion

**SECTION 13: Disposal considerations**

**13.1 Waste treatment methods**

**For the substance / mixture / residual amounts**

EC disposal code no.:  
 The waste codes are recommendations based on the scheduled use of this product.  
 Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)  
 07 01 04 other organic solvents, washing liquids and mother liquors  
 14 06 03 other solvents and solvent mixtures

Recommendation:  
 Sewage disposal shall be discouraged.  
 Pay attention to local and national official regulations.  
 E.g. suitable incineration plant.

**For contaminated packing material**

Pay attention to local and national official regulations.  
 Empty container completely.  
 Uncontaminated packaging can be recycled.  
 Dispose of packaging that cannot be cleaned in the same manner as the substance.

**SECTION 14: Transport information**

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0015  
 Replacing version dated / version: 09.10.2018 / 0014  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Engine Flush'n'Clean  
 300 ml Art.: 6750 7030, Art.: 6754 7030

### General statements

14.1. UN number or ID number: n.a.

### Transport by road/by rail (ADR/RID)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Classification code: n.a.

LQ: n.a.

14.5. Environmental hazards: Not applicable

Tunnel restriction code:

### Transport by sea (IMDG-code)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

Marine Pollutant: n.a.

14.5. Environmental hazards: Not applicable

### Transport by air (IATA)

14.2. UN proper shipping name:

14.3. Transport hazard class(es): n.a.

14.4. Packing group: n.a.

14.5. Environmental hazards: Not applicable

### 14.6. Special precautions for user

Unless specified otherwise, general measures for safe transport must be followed.

### 14.7. Maritime transport in bulk according to IMO instruments

Non-dangerous material according to Transport Regulations.

## SECTION 15: Regulatory information

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:

Comply with trade association/occupational health regulations.

Directive 2010/75/EU (VOC): 71,6 %

### REGULATION (EC) No 648/2004

30 % and more

aliphatic hydrocarbons

15 % or over but less than 30 %

aromatic hydrocarbons

less than 5 %

non-ionic surfactants

### 15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

## SECTION 16: Other information

Revised sections: 1-16

These details refer to the product as it is delivered.

Employee instruction/training in handling hazardous materials is required.

### Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

Classification in accordance with regulation (EC) No. 1272/2008 (CLP)	Evaluation method used
Asp. Tox. 1, H304	Classification according to calculation procedure.
Aquatic Chronic 3, H412	Classification according to calculation procedure.

Page 14 of 17  
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
Revision date / version: 01.11.2021 / 0015  
Replacing version dated / version: 09.10.2018 / 0014  
Valid from: 01.11.2021  
PDF print date: 01.11.2021  
Engine Flush'n'Clean  
300 ml Art.: 6750 7030, Art.: 6754 7030

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents (specified in Section 2 and 3).

H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.  
EUH066 Repeated exposure may cause skin dryness or cracking.

Asp. Tox. — Aspiration hazard  
Aquatic Chronic — Hazardous to the aquatic environment - chronic  
STOT SE — Specific target organ toxicity - single exposure - narcotic effects  
Skin Irrit. — Skin irritation  
Eye Irrit. — Eye irritation

### Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.  
Guidelines for the preparation of safety data sheets as amended (ECHA).  
Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).  
Safety data sheets for the constituent substances.  
ECHA Homepage - Information about chemicals.  
GESTIS Substance Database (Germany).  
German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).  
EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.  
National Lists of Occupational Exposure Limits for each country as amended.  
Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Förch SAS  
ZAE Le Marchais Renard  
CS 50125 Montereau-sur-le-Jard  
77019 Melun Cedex  
Frankreich  
Tel. +33 1 64 14 48 48  
Fax. +33 1 64 14 48 49  
E-Mail: [info@forch.fr](mailto:info@forch.fr)  
Internet: [www.forch.fr](http://www.forch.fr)

S.C. Foerch S.R.L.  
Str. Zizinului nr.110  
500407 Brasov  
Rumänien  
Tel. +40 368 408192  
Fax. +40 368 408193  
E-Mail: [info@foerch.ro](mailto:info@foerch.ro)  
Internet: [www.foerch.ro](http://www.foerch.ro)

Foerch AG  
Muttenerstrasse 143  
4133 Pratteln  
Schweiz  
Tel. +41 61 8262031  
Fax. +41 61 8262039  
E-Mail: [info@foerch.ch](mailto:info@foerch.ch)  
Internet: [www.foerch.ch](http://www.foerch.ch)

Foerch Bulgaria EOOD  
475 Botevgradsko Shose Blvd.  
BG 1517 Sofia, Bulgaria  
Tel. 00359 2 981 2841  
Fax. 00359 982 10 30 86  
E-Mail: [info@foerch.bg](mailto:info@foerch.bg)

Förch d.o.o.  
Buzinska cesta 58  
10010 Zagreb  
Kroatien  
Tel. +385 1 2912900  
Fax. +385 1 2912901  
E-Mail: [info@foerch.hr](mailto:info@foerch.hr)  
internet: [www.foerch.hr](http://www.foerch.hr)

Theo Förch GmbH  
Röcklbrunnstraße 39A  
5020 Salzburg  
Österreich  
Tel. +43 662 875574-0  
Fax +43 662 878677-21  
Verkauf Tel. +43 662 875574-900  
Verkauf Fax +43 662 875574-30  
E-Mail: [info@foerch.at](mailto:info@foerch.at)  
Internet: [www.foerch.at](http://www.foerch.at)

Förch Componentes para Taller S.L.  
Camino de San Antón, S/N  
18102 Ambroz (Granada)  
Spanien  
Tel. +34 958 40 17 76  
Fax. +34 958 40 17 87  
E-Mail: [info@forch.es](mailto:info@forch.es)  
Internet: [www.forch.es](http://www.forch.es)

Förch A/S  
Hagemannsvej 3  
8600 Silkeborg  
Dänemark  
Tel. +45 86 823711  
Fax. +45 86 800617  
E-Mail: [info@foerch.dk](mailto:info@foerch.dk)  
Internet: [www.foerch.dk](http://www.foerch.dk)

Lhomme Tools & Fasteners BV  
Seinhuisstraat 5 B4  
Poort 0331  
3600 Genk  
Belgien  
Tel. +32 89 71 66 61  
E-Mail: [info@lhommetools.be](mailto:info@lhommetools.be)  
Internet: [www.lhommetools.be](http://www.lhommetools.be)

Page 15 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0015

Replacing version dated / version: 09.10.2018 / 0014

Valid from: 01.11.2021

PDF print date: 01.11.2021

Engine Flush'n'Clean

300 ml Art.: 6750 7030, Art.: 6754 7030

Ziebe Limited  
7 Century Court, Westcott,  
Aylesbury, Bucks, HP18 0XP (UK)  
Grossbritannien  
Tel +44 12 96 65 52 82  
E-Mail: sales@ziebe.co.uk  
Internet: www.ziebe.co.uk

Förch Polska Sp. z o.o.  
Międzyrzecze Górne 379  
43-392 K/Bielska-Bialej  
Polen  
Tel. +48 338196000  
Fax. +48 338158548  
E-Mail: info@forch.pl  
Internet: www.forch.pl

Vardalis SM P.C.  
Ethnikis Antistasis 62  
57007 Chalkidona-Thessaloniki  
Griechenland  
Tel. +30 23910 21222  
Fax. +30 23910 21223  
E-Mail: info@forch.gr  
Internet: www.forch.gr

Förch Kereskedelmi Kft  
Börgöndi út 14  
8000 Székesfehérvár  
Ungarn  
Tel. +36 22 348348  
Fax. +36 22 348355  
E-Mail: info@foerch.hu  
Internet: www.foerch.hu

Förch S.r.l.  
Via Antonio Stradivari 4  
39100 Bolzano (BZ)  
Italien  
Tel: +39 0471 204330  
Fax: +39 0471 204290  
E-Mail: info@forch.it  
Internet: www.forch.it

Förch Nederland BV  
Twentepoort Oost 51  
7609 RG Almelo  
Niederlande  
Tel. +31 85 77 32 420  
E-Mail: info@foerch.nl  
Internet: www.foerch.nl

AB varahlutir ehf  
Funahöfði 9  
110 Reykjavík  
Tel. +354 567 6020  
E-mail: ab@ab.is  
Internet: www.ab.is

Förch Slovensko s.r.o.  
Rosinská cesta 8  
010 08 Žilina  
Slowakei  
Tel +421 41 5002454  
E-Mail: info@forch.sk  
Internet: www.forch.sk

Förch Sverige AB  
Brännarevägen 1  
151 55 Södertälje  
Schweden  
Tel. +46 855089264  
E-mail: info@foerch.se  
Internet: www.foerch.se

Förch, s.r.o.  
Dopravní 1314/1  
104 00 Praha 10 – Uhřetíněves  
Tschechien  
Tel. +420 271 001 984-9  
E-Mail: info@foerch.cz  
Internet: www.foerch.cz

FORCH d.o.o.  
Ljubljanska cesta 51A  
1236 Trzin  
Slowenien  
Tel. +386 1 2442490  
Fax. +386 1 2442492  
E-Mail: info@foerch.si  
Internet: www.foerch.si

Forch Australia  
2 Forward Street  
Gnangara WA 6077  
Tel. +61 (08) 9303 9113  
Fax. +61 (08) 9303 9114  
Emergency telephone: +614 13 550 330  
Email : sales@forch.com.au  
Internet: www.forch.com.au

Troscoe Ltd  
Unit 6, 13 Highbrook Drive  
East Tamaki 2013, New Zealand  
Tel: +64 21 081 30780 / +64 21 024 05583  
Email:sales@forchnz.co.nz  
Internet: www.forchnz.co.nz

Förch Portugal Lda  
Centro Empresarial Sintra-Estoril III  
Rua Pé de Mouro, Nr 33, Armazém J  
2710-335 Sintra  
Portugal  
Tel. +351 917314442  
E-Mail: info@forch.pt  
Internet: www.forch.pt

Trigers SIA  
Straupes iela 3  
1073 Rīga  
Lettland  
Tel. +371 6 7 90 25 15  
Fax. +371 67 90 24 96  
E-Mail: triggers@trigers.lv  
Internet: www.trigers.lv

Förch Otom.Ins.ve San.Ürün.Paz.Ltd.Sti.  
Haramidere Mevkii Beysan Sanayi  
Sitesi Birlik Caddesi No:6/3  
34524 Beylikdüzü / Istanbul  
Türkei  
Tel. +90 (0)212 422 8744-45  
Fax. +90 (0)212 422 8788  
E-Mail: info@forch.com.tr  
Internet: www.forch.com.tr

Total Consumables Ltd  
Coolnafearagh  
Monasterevin  
Co. Kildare  
W34 TX29  
Irland  
Tel. +353871271473

Venus Arma d.o.o.  
Partner Theo Förch GmbH & Co. KG  
Batajnicki drum 18a  
11080 Zemun  
Republika Srbija  
Tel. +381 11 407-20-91  
Fax. +381 11 407-20-91  
E-Mail: office@foerch.rs  
Internet: www.foerch.rs

### Any abbreviations and acronyms used in this document:

acc., acc. to      according, according to

Page 16 of 17  
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II  
 Revision date / version: 01.11.2021 / 0015  
 Replacing version dated / version: 09.10.2018 / 0014  
 Valid from: 01.11.2021  
 PDF print date: 01.11.2021  
 Engine Flush'n'Clean  
 300 ml Art.: 6750 7030, Art.: 6754 7030

ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)  
 AOX Adsorbable organic halogen compounds  
 approx. approximately  
 Art., Art. no. Article number  
 ASTM ASTM International (American Society for Testing and Materials)  
 ATE Acute Toxicity Estimate  
 BAM Bundesanstalt für Materialforschung und -prüfung (Federal Institute for Materials Research and Testing, Germany)  
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)  
 BCF Bioconcentration factor  
 BSEF The International Bromine Council  
 bw body weight  
 CAS Chemical Abstracts Service  
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)  
 CMR carcinogenic, mutagenic, reproductive toxic  
 DMEL Derived Minimum Effect Level  
 DNEL Derived No Effect Level  
 DOC Dissolved organic carbon  
 dw dry weight  
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance  
 EbCx, EyCx, EBLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)  
 EC European Community  
 ECHA European Chemicals Agency  
 ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect  
 EEC European Economic Community  
 EINECS European Inventory of Existing Commercial Chemical Substances  
 ELINCS European List of Notified Chemical Substances  
 EN European Norms  
 EPA United States Environmental Protection Agency (United States of America)  
 ErCx, EµCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)  
 etc. et cetera  
 EU European Union  
 EVAL Ethylene-vinyl alcohol copolymer  
 Fax. Fax number  
 gen. general  
 GHS Globally Harmonized System of Classification and Labelling of Chemicals  
 GWP Global warming potential  
 Koc Adsorption coefficient of organic carbon in the soil  
 Kow octanol-water partition coefficient  
 IARC International Agency for Research on Cancer  
 IATA International Air Transport Association  
 IBC (Code) International Bulk Chemical (Code)  
 IMDG-code International Maritime Code for Dangerous Goods  
 incl. including, inclusive  
 IUCLID International Uniform Chemical Information Database  
 IUPAC International Union for Pure Applied Chemistry  
 LC50 Lethal Concentration to 50 % of a test population  
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)  
 Log Koc Logarithm of adsorption coefficient of organic carbon in the soil  
 Log Kow, Log Pow Logarithm of octanol-water partition coefficient  
 LQ Limited Quantities  
 MARPOL International Convention for the Prevention of Marine Pollution from Ships  
 n.a. not applicable  
 n.av. not available  
 n.c. not checked  
 n.d.a. no data available  
 NIOSH National Institute for Occupational Safety and Health (USA)  
 NLP No-longer-Polymer  
 NOEC, NOEL No Observed Effect Concentration/Level  
 OECD Organisation for Economic Co-operation and Development  
 org. organic  
 OSHA Occupational Safety and Health Administration (USA)  
 PBT persistent, bioaccumulative and toxic  
 PE Polyethylene  
 PNEC Predicted No Effect Concentration

Page 17 of 17

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 01.11.2021 / 0015

Replacing version dated / version: 09.10.2018 / 0014

Valid from: 01.11.2021

PDF print date: 01.11.2021

Engine Flush'n'Clean

300 ml Art.: 6750 7030, Art.: 6754 7030

ppm parts per million

PVC Polyvinylchloride

REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)

REACH-IT List-No. 9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.

RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)

SVHC Substances of Very High Concern

Tel. Telephone

TOC Total organic carbon

UN RTDG United Nations Recommendations on the Transport of Dangerous Goods

VOC Volatile organic compounds

vPvB very persistent and very bioaccumulative

wwt wet weight

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.

No responsibility.

These statements were made by:

**Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90**

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.